

Active Optical (AOC) High speed HDMI cable with Ethernet "AOC Premium Series", 30 m

CCBP-HDMI-AOC-30M

- HDMI Active Optical Cable (AOC) uses fiber optic technology to transport the digital HDMI signal. This means that the signal can be carried much further than with a traditional copper cable (up to 100 m), and reduces the risk of EMI/RFI interference. HDMI AOC cables also have dedicated copper power wires inside, so no external power supply is
- required.
- HDMI AOC cable uses fiber optic technology reduces the risk of EMI/RFI in high interference environments
- Durable extra thin premium quality braided cable with stylish metal connectors
- Smaller cable diameter compared to traditional copper HDMI cables
- Supports 4K UHD resolutions at 60Hz

Features

- Premium High Speed HDMI AOC cable with Ethernet
- Supports HDMI 2.0 4K UHD resolutions at 60 Hz
- Fiber optic cable is highly resistant to EMI and RFI interference
- Durable nylon braiding and premium metal connectors
- Gold plated connectors for perfect image quality
- Compatible with all devices that support HDMI

Packaging

Q'ty in crtn, pcs Crtn volume, CUM Crtn weight, kgs Individual package size LxWxH: Carton size LxWxH: Country of origin Barcode Customs code 10 0.027 9.18 200x250x50 mm 425x225x280 mm CN 8716309109093 8544429090

Certificates











Specifications

Type: AOC, High-speed HDMI with Ethernet Supported HDMI versions: HDMI 2.0 (and all previous versions)

Connector 1: HDMI Type-A male, straight, gold plated Connector 2: HDMI Type-A male, straight, gold plated Conductor material: fiber optical + CU

Maximum bandwidth: 18 Gbps

 $\label{eq:maximum supported resolution: 4K @ 60Hz} \\ \text{Supported features: CEC, HEC, HARC, HDR, EDID, 3D}$

21:9 cinema aspect ratio: supported YCbCr 4:2:2/4:4:4/4:2:0: supported

Deep Color: supported (up to 16-bits per channel)

Audio support: PCM, DTS-HD Master, and Dolby Digital True HD Surround

Sound compatible

Audio channel support: 32 channels HDCP support: version 1.4 / 2.2

Jacket braiding: n.a.

Jacket outer diameter: 9,5 mm

Connector style: metal

Length: 30 m