

# Active Optical (AOC) High speed HDMI cable with Ethernet "AOC Premium Series", 80 m

## CCBP-HDMI-AOC-80M

- HDMI Active Optical Cable (AOC) uses fiber optic technology to transport the digital HDMI signal. This means that the signal can be carried much further than with a traditional copper cable (up to 100 m), and reduces the risk of EMI/RFI interference. HDMI AOC cables also have dedicated copper power wires inside, so no external power supply is
- required.
- HDMI AOC cable uses fiber optic technology reduces the risk of EMI/RFI in high interference environments
- Durable extra thin premium quality braided cable with stylish metal connectors
- Smaller cable diameter compared to traditional copper HDMI cables
- Supports 4K UHD resolutions at 60Hz

#### **Features**

- Premium High Speed HDMI AOC cable with Ethernet
- Supports HDMI 2.0 4K UHD resolutions at 60 Hz
- Fiber optic cable is highly resistant to EMI and RFI interference
- Durable nylon braiding and premium metal connectors
- Gold plated connectors for perfect image quality
- Compatible with all devices that support HDMI

### Packaging

Q'ty in crtn, pcs Crtn volume, CUM Crtn weight, kgs Individual package size LxWxH: Carton size LxWxH: Country of origin Barcode Customs code

10 0.061 26.09 260x260x70 mm 555x285x385 mm CN 8716309109116 8544429090

### Certificates





#### **Specifications**

Type: AOC, High-speed HDMI with Ethernet Supported HDMI versions: HDMI 2.0 (and all previous versions)

Connector 1: HDMI Type-A male, straight, gold plated Connector 2: HDMI Type-A male, straight, gold plated Conductor material: fiber optical + CU Maximum bandwidth: 18 Gbps Maximum supported resolution: 4K @ 60Hz Supported features: CEC, HEC, HARC, HDR, EDID, 3D 21:9 cinema aspect ratio: supported YCbCr 4:2:2/4:4:4/4:2:0: supported Deep Color: supported (up to 16-bits per channel) Audio support: PCM, DTS-HD Master, and Dolby Digital True HD Surround Sound compatible Audio channel support: 32 channels HDCP support: version 1.4 / 2.2 Jacket braiding: n.a. Jacket outer diameter: 9,5 mm Connector style: metal Length: 80 m