

# S/FTP Cat. 8 LSZH patch cord, black, 0.25 m

PP8-LSZHCU-BK-0.25M



## **Specifications**

Category: category 8 Type: SSTP (shielded) Frequency bandwith: Max. 2000 MHz Compliance with ANSI / TIA / EIA-568B standards Conductor: AWG 27 (7 x 0.135 mm wire), COPPER Conductor insulation: FM-PE 1.0 mm Shielding: AL foil + braid shield (16 x 5/0.12 mm) LDPE filler: yes Polyester tape: yes Drain wire: n/a Jacket material: LSZH Jacket braiding n/a Jacket outer diameter: 5.8 mm

Length: conform item description Color: conform item description

- Perfect connection
- Dual shielded for a reliable connection
- Low Smoke Zero Halogen (LSZH) jacket
- Gold plated connectors and contacts

#### **Features**

- Patch cord with foil shielded pairs and braided cable, CAT 8
- Gold plated connectors and contacts
- Low Smoke Zero Halogen (LSZH) jacket
- Molded strain reliefs
- Snagless boots

### **Packaging**

Q'ty in crtn, pcs 400 Crtn volume, CUM 0.04 Crtn weight, kgs 7.61 Individual package size LxWxH: 125x10x180 mm Carton size LxWxH: 400x300x330 mm Country of origin CN Barcode 8716309119771 Customs code 8544421000

#### **Certificates**











