


S/FTP Cat. 8 LSZH patch cord, black, 3 m

PP8-LSZHCU-BK-3M

- Perfect connection
- Dual shielded for a reliable connection
- Low Smoke Zero Halogen (LSZH) jacket
- Gold plated connectors and contacts



Specifications

Category: category 8
 Type: SFTP (shielded)
 Frequency bandwidth: Max. 2000 MHz
 Compliance with ANSI / TIA / EIA-568B standards
 Conductor: AWG 27 (7 x 0.135 mm wire), COPPER
 Conductor insulation: FM-PE 1.0 mm
 Shielding: AL foil + braid shield (16 x 5/0.12 mm)
 LDPE filler: yes
 Polyester tape: yes
 Drain wire: n/a
 Jacket material: LSZH
 Jacket braiding n/a
 Jacket outer diameter: 5.8 mm
 Length: conform item description
 Color: conform item description

Features

- Patch cord with foil shielded pairs and braided cable, CAT 8
- Gold plated connectors and contacts
- Low Smoke Zero Halogen (LSZH) jacket
- Molded strain reliefs
- Snagless boots

Packaging

Q'ty in crtn, pcs	80
Crtn volume, CUM	0.038
Crtn weight, kgs	8.34
Individual package size LxWxH:	175x125x10 mm
Carton size LxWxH:	410x310x300 mm
Country of origin	CN
Barcode	8716309120654
Customs code	8544421000

Certificates

