

# FTP Cat6 Patch cord, grey, 20 m

PPB6-20M

- CAT6 AWG26 stranded foil shielded patch cord with moulded strain relief 50u" 8P8C plugs, 20m



## Specifications

Category: category 6  
 Type: FTP (foil shielded)  
 Frequency bandwidth: Max. 250 MHz  
 Compliance with ANSI / TIA / EIA-568B standards  
 Conductor: AWG 26 (7 x 0.15 mm wire), CCA  
 Conductor insulation: HDPE 0.86 mm  
 Shielding: AL foil  
 LDPE filler: yes  
 Polyester tape: yes  
 Drain wire: yes (7 x 0.12 mm CCA)  
 Jacket material: PVC  
 Jacket braiding: n/a  
 Jacket outer diameter: 6.2 mm  
 Length: conform item description  
 Color: conform item description

## Packaging

|                                |                |
|--------------------------------|----------------|
| Q'ty in crtn, pcs              | 20             |
| Crtn volume, CUM               | 0.06           |
| Crtn weight, kgs               | 12.02          |
| Individual package size LxWxH: | 196x195x54 mm  |
| Carton size LxWxH:             | 420x428x334 mm |
| Country of origin              | CN             |
| Barcode                        | 8716309121514  |
| Customs code                   | 8544421000     |

## Certificates

