


CAS-241

Automatic CPU switch w/audio support, 2 PCs

- Automatic CPU switch with Audio support



Features

- 1. PS/2 (AT) keyboard and mouse emulation.
- 2. Switching of the PCs stereo audio channels.
- 3. Optional SwitchSound mode switching of the PCs stereo audio channels.
- 4. Additional buzzer and LED indication of the sound event.
- 5. Optional HoldSoundEvent mode – indication of the sound event will be continued until the channel is selected.
- 6. Plug and Play keyboard and mouse initialization.
- 7. Hot-plug connection of the computers without need to reboot.

Packaging

| | |
|--------------------------------|----------------|
| Q'ty in crtn, pcs | 20 |
| Crtn volume, CUM | 0.031 |
| Crtn weight, kgs | 11.8 |
| Individual package size LxWxH: | 155x55x145 mm |
| Carton size LxWxH: | 590x310x170 mm |
| Country of origin | CN |
| Barcode | 8716309023207 |
| Customs code | 8536508090 |

Specifications

Number of switching computers: 2

Mouse and keyboard protocol emulation: PS/2 keyboard, PS/2 mouse, PC/AT keyboard

Case design: Desktop

Case housing: Metal with plastic front panel

Computer selection: Push buttons or keyboard hot keys

Computer side connectors: HD-15Mx2, MD-6Fx4, 3.5 mm stereo audio jack x 2

Console side connectors: HD-15Mx1, MD-6Fx2, 3.5 mm stereo audio jack x 1

Front panel LEDs

System requirements

Console requirements:

VGA, SVGA, or Multisync monitor supporting the highest resolution among all the PCs connected to the switch

PS/2 compatible mouse

PS/2 compatible keyboard

Computers requirements:

VGA, SVGA or Multisync video card

Certificates

