

CAS-441

Automatic CPU and audio switch, 4 PCs

- World of ideas
- Enables one set of keyboard/monitor/mouse to control 4 PCs
- Computers selectable by means of a push button or keyboard hot keys
- Also switches audio
- Save space and money in multi-computer environments
- Suitable for any operating system



Features

- Switching of the PCs stereo audio channels
- Optional SwitchSound mode switching of the PCs stereo audio channels
- Additional buzzer and LED indication of the sound event
- Optional HoldSoundEvent mode – indication of the sound event will be continued until the channel is selected
- Plug and Play keyboard and mouse initialization
- Hot-plug connection of the computers without need to reboot
- PC switching via front panel pushbuttons or keyboard hot keys
- No software required

Packaging

Q'ty in crtn, pcs	20
Crtn volume, CUM	0.046
Crtn weight, kgs	16.6
Individual package size LxWxH:	255x54x145 mm
Carton size LxWxH:	300x500x310 mm
Country of origin	CN
Barcode	8716309026062
Customs code	8536508090

Certificates



Specifications

Number of switching computers: 4
 Mouse and keyboard protocol emulation: PS/2 keyboard, PS/2 mouse, PC/AT keyboard
 Case design: Desktop
 Case housing: Metal with plastic front panel
 Computer selection: Push buttons or keyboard hot keys
 Computer side connectors: HD-15Mx4, MD-6Fx8, 3.5 mm stereo audio jack x 4
 Console side connectors: HD-15Mx1, MD-6Fx2, 3.5 mm stereo audio jack x 1

Front panel LEDs per channel: "Link/Event", "Active/Scan"

Audio channels type: Stereo
 Standard PS/2 mouse, 3-buttons, scrolling wheel, Microsoft®, Logitech®, A4Tech®, Genius® 4-5 buttons mice support
 Keyboard LEDs status saving and restoring
 Mode and event LED indication
 AutoScan mode with intervals 4,10,30 secs
 Video resolution up to 2048x1536, video bandwidth 250 MHz, DDC, DDC2, DDC2B
 Computer boot-up LED indication
 Audio frequency ban

System requirements

Console requirements:
 VGA, SVGA, or Multisync monitor supporting the highest resolution among all the PCs connected to the switch
 PS/2 compatible mouse
 PS/2 compatible keyboard
 Computers requirements:
 VGA, SVGA or Multisync video card
 6-pin mini-DIN (PS/2) mouse port
 6-pin mini-DIN (PS/2) keyboard port
 Cables required:
 Male-to-male VGA cables
 Male-to-male Mini-DIN 6 pin cables