

NSW-R2 802.11G 54M 1 WAN + 4 LAN ports WiFi broadband router



#### Features

- All-in-one: internet-sharing router, 4-port 10/100Mbps LAN switch and 802.11g access point
- Complies with IEEE802.11g, IEEE802.11b, IEEE802.3, IEEE802.3u standards
- Allows to share a single Internet connection and other resources among Ethernet wired and wireless clients
- Built-in DHCP server automatically assigns and manages LAN IP addresses
- Wireless data transfer rate up to 54Mbps via 802.11g protocol, and downwards compatible with 802.11b protocol up to 11Mbps
- Supports 64/128-bit WEP encryption security

### Packaging

Q'ty in crtn, pcs Crtn volume, CUM Crtn weight, kgs Individual package size LxWxH: Carton size LxWxH: Country of origin Barcode Customs code 20 0.09315 13.8 202x124x36 mm 600x345x450 mm CN 8716309043939 8522900090

### **Package contents**

Broadband router Power adapter User manual

### Certificates



## System requirements

System requirements for wired connections: DSL/Cable Modem 10/100M Ethernet LAN card and TCP/IP network protocol on each computer RJ45 twisted-pair CAT5e cable network

#### Copyright © 2009–2024, Gembird Software Ltd.

Gembird Europe B.V. Wittevrouwen 56, 1358CD Almere, The Netherlands. Phone: +31-36-5211588

# **Specifications**

Operates in the 2.4GHz frequency range Radio-frequency data: power 20 dBm (max. EIRP), 5 dBi fixed antenna

Supports DHCP/Static IP/PPPoE protocols, PPPoE auto-connect and autodisconnect Supports IP filter, URL filter, Port filter, and MAC address filter

Supports wireless LAN ACL (Access Control List) filtering Supports WPA/WPA2 and WPA-PSK/WPA2-PSK authentication and TKIP/AES encryption security Supports time schedule Supports MAC address and IP address binding, MAC address CLONE

Supports Static Route, WDS, Dynamic DNS Supports UpnP, Virtual server, DMZ host Supports VPN Passthrough for IPSec, PPTP and L2TP Protocols

Supports TCP/IP, PPPoE, DHCP, ICMP, NAT, SNTP, ARP Protocols

Supports security logs Transmission distance: indoor up to 120m, outdoor up to 360m, depending on the environment Dimensions: 202x124x36mm Weight: 0.32kg Power adapter: 5VDC, 2A Storage: -40?C ~70?C, at 5% ~95% humidity Operating temperature: -10?C ~50?C at 10%~90% humidity