energenie

GREEN ENERGY FOR A BLUE PLANET

1200VA UPS with AVR, advanced

UPS-PC-1202AP



ULTIMATE DEFENCE

- Provides backup power prevents data loss
- Protects your sensitive and valuable equipment
- Compact and reliable ideal for home and small office use

Specifications

UPS type: line interactive
Input: AC 162 295 V, 50 Hz / 60 Hz ± 10 %
Output: AC 188 254 V, 50 Hz / 60 Hz ± 0.5 % (on battery)
Waveform: sine wave (AC mains), simulated sine wave (battery)

Temperature compensation: -20mV/1 °C (per cell)
Switching time: no more than 5 ms
Backup time: 2...20 mins (depends on the load)
Battery: sealed lead-acid 12V/7Ah x 2pcs
Charge time: up to 12 hours
Sockets: 1x input (C14), 4x output (C13 / Shuko optional); 2x telephone RJ11 connectors; 1x USB-BF connector
Operating conditions: 0°C~40°C, at humidity 20~90 %RH non condensing

Power: 1200 VA (720 W)
Dimensions: 382 x 222 x 124 mm
Product weight: 10.4 kg
"Cold-start" function

Features

- Uninterruptable 1200 VA power supply for PC's
- Automatic output voltage regulation (AVR)
- USB interface
- LED status indication
- Short circuit protection
- Surge, spike and lightning protection
- Audible and visual alarms
- Overcharge and overdischarge protection
- Fax/Modem/Telephone protection socket
- Including Practical UPS Management software

Packaging

Q'ty in crtn, pcs	2
Crtn volume, CUM	0.0465
Crtn weight, kgs	22.54
Individual package size LxWxH:	390x185x295 mm
Carton size LxWxH:	400x375x310 mm
Country of origin	CN
Barcode	8716309047814
Customs code	8504408590

Package contents

UPS
Power cord
USB cable
Software CD
Spare fuse

Certificates

System requirements

Software is compatible with Windows 7, Windows 2008 server, Windows 8/10

In order to work correclty, the connected load should be at least 5% of the

Copyright © 2009–2024, Gembird Software Ltd.

Wittevrouwen 56 | 1358CD Almere | The Netherlands | Phone: +31-36-5211588
www.energenie.com | postmaster@energenie.com