# 1200VA UPS with AVR, advanced

UPS-PC-1202AP

## ULTIMATE DEFENCE

- Provides backup power prevents data loss
- Protects your sensitive and valuable equipment
- Compact and reliable ideal for home and small office use



## Specifications

UPS type: line interactive
Input: AC 162 295 V, 50 Hz / 60 Hz ± 10 %
Output: AC 188 254 V, 50 Hz / 60 Hz  ± 0.5 % (on battery)
Waveform: sine wave (AC mains), simulated sine wave (battery)

Temperature compensation:  -20mV/1 °C (per cell)
Switching time: no more than 5 ms
Backup time: 2...20 mins (depends on the load)
Battery: sealed lead-acid 12V/7Ah x 2pcs
Charge time: up to 12 hours
Sockets: 1x input (C14), 4x output (C13 / Shuko optional);  2x telephone RJ11 connectors; 1x USB-BF connector
Operating conditions: 0°C~40°C, at humidity 20~90 %RH non condensing

Power: 1200 VA (720 W)
Dimensions: 382 x 222 x 124 mm
Product weight: 10.4 kg
"Cold-start" function

## Features

- Uninterruptable 1200 VA power supply for PC's
- Automatic output voltage regulation (AVR)
- USB interface
- LED status indication
- Short circuit protection
- Surge, spike and lightning protection
- Audible and visual alarms
- Overcharge and overdischarge protection
- Fax/Modem/Telephone protection socket
- Including Practical UPS Management software

## Packaging

| | |
|---|---|
| Q'ty in crtn, pcs | 2 |
| Crtn volume, CUM | 0.0465 |
| Crtn weight, kgs | 22.54 |
| Individual package size LxWxH: | 390x185x295 mm |
| Carton size LxWxH: | 400x375x310 mm |
| Country of origin | CN |
| Barcode | 8716309047814 |
| Customs code | 8504408590 |

## Package contents

UPS
Power cord
USB cable
Software CD
Spare fuse

## Certificates



## System requirements

Software is compatible with Windows 7, Windows 2008 server, Windows 8/10

In order to work correclty, the connected load should be at least 5% of the