
FTP Cat5e Patch cord, green, 0.5 m

PP22-0.5M/G



Features

- Foil shielded twisted pair patch cord

Specifications

Category: Enhanced category 5
Type: FTP (foil shielded)
Frequency bandwidth: Max. 100 MHz
Compliance with ANSI / TIA / EIA-568B standards
Conductor: AWG 26 (7 x 0.15 mm wire), CCA
Conductor insulation: HDPE 0.85 mm
Shielding: AL foil
LDPE filler: n/a
Polyester tape: yes
Drain wire: yes (7 x 0.12 mm CCA)
Jacket material: PVC
Jacket braiding: n/a
Jacket outer diameter: 5.0 mm
Length: conform item description
Color: conform item description

Packaging

Q'ty in crtn, pcs	350
Crtn volume, CUM	0.038
Crtn weight, kgs	8.8
Individual package size LxWxH:	120x100x20 mm
Carton size LxWxH:	395x385x250 mm
Country of origin	CN
Barcode	8716309052061
Customs code	8544421000

Certificates

Copyright © 2009–2022, Gembird Software Ltd.

Wittevrouwen 56 | 1358CD Almere | The Netherlands | Phone: +31-36-5211588 | www.cablexpert.com | postmaster@cablexpert.com