Remote controlled surge protector

SPG-RM V2

- Basic surge protector
- Extends AC power supply
- Protects valuable equipment
- Wireless remote controllable



Specifications

Input voltage: 250 VAC, 50 Hz
Maximum load: 10 A current, up to 2500 VA
Maximum energy dissipation: 150 Joules
Surge protector standby power: <= 0.8 W, at AC 250 V
Remote controllor standby current: <=3 uA, at DC 12 V
Radio-frequency remote controller: transmission frequecy 433.92 MHz, operation distance up to 10 m, encoded control signal with more than 6500 combinations, 12 V battery ("23A" type) included

Working temperature range: +10 ... +40 degrees Celsius
German Schuko type sockets: 5 pcs
Power cord: 6 ft, 10 A, VDE approved
Dimensions: 325 x 50 x 40 mm
Weight: 0.43 kg

Features

- 5 socket AC power surge protector with 10 m remote control
- Protects computers, other office equipment and home appliances from harmful power surges and spikes
- Maximum load: 10 A current, up to 2500 VA
- Maximum energy dissipation: 150 Joules
- 5 AC sockets German type
- Top quality, flame retardant plastic case
- Children protection
- Mounting holes
- VDE-approved German plug power cord

Packaging

Q'ty in crtn, pcs	20
Crtn volume, CUM	0.095589
Crtn weight, kgs	14.4
Individual package size LxWxH:	140x45x410 mm
Carton size LxWxH:	645x390x380 mm
Country of origin	CN
Barcode	8716309064064
Customs code	8544429090

Package contents

Surge protector
Remote controller

Certificates

Copyright © 2009–2024, Gembird Software Ltd.

Wittevrouwen 56 | 1358CD Almere | The Netherlands | Phone: +31-36-5211588
www.energenie.com | postmaster@energenie.com