

Remote controlled surge protector SPG-RM V2

- Basic surge protector
- Extends AC power supply
- Protects valuable equipment
- Wireless remote controllable
- Euro 20000 insurance for attached peripherals included, conditions



Features

- 5 socket AC power surge protector with 10 m remote control
- Protects computers, other office equipment and home appliances from harmful power surges and spikes
- Maximum load: 10 A current, up to 2500 VA
- Maximum energy dissipation: 150 Joules
- 5 AC sockets German type
- Top quality, flame retardant plastic case
- Children protection
- Mounting holes
- VDE-approved German plug power cord

Packaging

Q'ty in crtn, pcs
Crtn volume, CUM
Crtn weight, kgs
Individual package size LxWxH:
Carton size LxWxH:
Country of origin
Barcode
Customs code

20
0.095589
14.4
140x45x410 mm
645x390x380 mm
CN
8716309064064
8544429090

Package contents

Surge protector
Remote controller

Specifications

Input voltage: 250 VAC, 50 Hz
Maximum load: 10 A current, up to 2500 VA
Maximum energy dissipation: 150 Joules
Surge protector standby power: ≤ 0.8 W, at AC 250 V
Remote controller standby current: ≤ 3 μ A, at DC 12 V
Radio-frequency remote controller: transmission frequency 433.92 MHz, operation distance up to 10 m, encoded control signal with more than 6500 combinations, 12 V battery ("23A" type) included

Working temperature range: +10 ... +40 degrees Celsius
German Schuko type sockets: 5 pcs
Power cord: 6 ft, 10 A, VDE approved

Certificates

