

Remote controlled surge protector

SPG-RM V2

- Basic surge protector
- Extends AC power supply
- Protects valuable equipment
- Wireless remote controllable



Features

- 5 socket AC power surge protector with 10 m remote control
- Protects computers, other office equipment and home appliances from harmful power surges and spikes
- Maximum load: 10 A current, up to 2500 VA
- Maximum energy dissipation: 150 Joules
- 5 AC sockets German type
- Top quality, flame retardant plastic case
- Children protection
- Mounting holes
- VDE-approved German plug power cord

Packaging

| | |
|--------------------------------|----------------|
| Q'ty in crtn, pcs | 20 |
| Crtn volume, CUM | 0.095589 |
| Crtn weight, kgs | 14.4 |
| Individual package size LxWxH: | 140x45x410 mm |
| Carton size LxWxH: | 645x390x380 mm |
| Country of origin | CN |
| Barcode | 8716309064064 |
| Customs code | 8544429090 |

Package contents

Surge protector
Remote controller

Specifications

Input voltage: 250 VAC, 50 Hz
Maximum load: 10 A current, up to 2500 VA
Maximum energy dissipation: 150 Joules
Surge protector standby power: ≤ 0.8 W, at AC 250 V
Remote controller standby current: ≤ 3 μ A, at DC 12 V
Radio-frequency remote controller: transmission frequency 433.92 MHz, operation distance up to 10 m, encoded control signal with more than 6500 combinations, 12 V battery ("23A" type) included

Working temperature range: +10 ... +40 degrees Celsius
German Schuko type sockets: 5 pcs
Power cord: 6 ft, 10 A, VDE approved
Dimensions: 325 x 50 x 40 mm
Weight: 0.43 kg

Certificates

