

# Remote controlled surge protector

SPG-RM V2

- Basic surge protector
- Extends AC power supply
- Protects valuable equipment
- Wireless remote controllable



**Specifikacije** 

Input voltage: 250 VAC, 50 Hz

Maximum load: 10 A current, up to 2500 VA Maximum energy dissipation: 150 Joules

Surge protector standby power: <= 0.8 W, at AC 250 V Remote controllor standby current: <=3 uA, at DC 12 V

combinations, 12 V battery ("23A" type) included

German Schuko type sockets: 5 pcs

Power cord: 6 ft, 10 A, VDE approved

Dimensions: 325 x 50 x 40 mm

Weight: 0.43 kg

Working temperature range: +10 ... +40 degrees Celsius

Radio-frequency remote controller: transmission frequecy 433.92 MHz, operation distance up to 10 m, encoded control signal with more than 6500

## Karakteristike

- 5 socket AC power surge protector with 10 m remote control
- Protects computers, other office equipment and home appliances from harmful power surges and spikes
- Maximum load: 10 A current, up to 2500 VA
- Maximum energy dissipation: 150 Joules
- 5 AC sockets German type
- Top quality, flame retardant plastic case
- Children protection
- Mounting holes
- VDE-approved German plug power cord

## Pakovanje i slike

Q'ty in crtn, pcs Crtn volume, CUM Crtn weight, kgs Individual package size LxWxH: Carton size LxWxH: Country of origin Barcode Customs code

0.095589 14.4 140x45x410 mm 645x390x380 mm CN 8716309064064 8544429090

#### **Package contents**

Surge protector Remote controller

#### Sertifikati











Copyright © 2009-2024, Gembird Software Ltd.