

Remote controlled surge protector

SPG-RM V2

- Basic surge protector
- Extends AC power supply
- Protects valuable equipment
- Wireless remote controllable



Propriétés

- Mise en route/ Arrêt du Boîtier Multiprise (5 prises), télécommandé
- Interrupteur de sécurité manuel Marche/Arrêt
- LED indicateur de l'état
- Cordon de raccordement certifié VDE pour forte charge

Spécificités

Input voltage: 250 VAC, 50 Hz
 Maximum load: 10 A current, up to 2500 VA
 Maximum energy dissipation: 150 Joules
 Surge protector standby power: ≤ 0.8 W, at AC 250 V
 Remote controller standby current: ≤ 3 μ A, at DC 12 V
 Radio-frequency remote controller: transmission frequency 433.92 MHz, operation distance up to 10 m, encoded control signal with more than 6500 combinations, 12 V battery ("23A" type) included

Working temperature range: +10 ... +40 degrees Celsius
 German Schuko type sockets: 5 pcs
 Power cord: 6 ft, 10 A, VDE approved
 Dimensions: 325 x 50 x 40 mm
 Weight: 0.43 kg

Packaging

Q'ty in crtn, pcs	20
Crtn volume, CUM	0.095589
Crtn weight, kgs	14.4
Individual package size LxWxH:	140x45x410 mm
Carton size LxWxH:	645x390x380 mm
Country of origin	CN
Barcode	8716309064064
Customs code	8544429090

Contenu du colis

Surge protector
 Remote controller

Certificats

