

Switching power distribution unit (PDU), 1U rack, 16A, C13 outlet x 8 pcs

EG-PDU-002

- Remote management:
 - Allows users to access, configure, and manage the PDU from remote locations via SSL web (https) and SNMP control. Reduce system down-time and simply reboot from a remote location with a simple switch of one individual power socket. The possibility of switching individual sockets finally makes remote control a reality. Your switch is my command!
- Magic of metering:
 - True RMS Current Metering & Reporting. Prevents overloaded circuits and allows allocating energy costs to specific devices. Monitor energy usage of the total PDU via the LED display, or from any remote location with the network management capabilities of the PDU.
- Real time alarm system:
 - Real time sensing of user defined alarm thresholds helps avoiding overloaded circuits. The PDU informs users about alarm situations via e-mail, SNMP, SysLog and visible (LED) and audible alarm signals.
- Protects your equipment:
 - Advanced circuit breaker protection helps protecting your valuable equipment.
- Wide product range:



Features

- Remote Power Management
- SNMP Control and SSL Web Browser (Https) for Setup and management
- Remote Total PDU Power Monitoring
- True RMS Current Metering & Reporting
- Alarm Threshold Sensing
- User Defined Alarm Thresholds
- Alarm Notification via Email, SNMP, Syslog, LED or Audible Alarm.
- User Defined Power On/OFF Sequence Time.
- Memorized Power-Up Previous Status

Packaging

Q'ty in crtn, pcs	6
Crtn volume, CUM	0.072
Crtn weight, kgs	15.76
Individual package size LxWxH:	510x210x90 mm
Carton size LxWxH:	520x460x300 mm
Country of origin	TW
Barcode	8716309067461
Customs code	8537109899

Specifications

RJ45:1pcs;10M Ethernet;ICMP, ARP, IP, TCP, UDP, DHCP, HTTP, HTTPS, SNMPv1
 Reset Hole:1pcs;Hardware Reset;
 Button:1pcs;Function;1 beeps : Current, Temp./Humidity Display 2 Beeps : IP Display. 4 Beeps : DHCP/Fixed 6 Beeps : Reset to Default

Seven Segments3 digits;CurrentTrue RMS Meter Range: 0A ~ 20 A
 Resolution: 0.1A Precision: +/-2%/+/-0.1AMP
 IPPress Button after 2 Beeps will display PDU IP Address
 Yellow LED:1pcs;ON: SSLis enabled
 Green LED:1pcs;IPON: DHCP is enabled
 Green LED:8pcs;Power Status
 Output:8pcs;IEC320 C13 x 8

Certificates

