

Per-outlet-metering power distribution unit (POM PDU), 1U rack, 32A, C13 outlet x 8 pcs, C20 input

EG-PDU-007

- Remote management:
 - Allows users to access, configure, and manage the PDU from remote locations via SSL web (https) and SNMP control. Reduce system downtime and simply reboot from a remote location with a simple switch of one individual power socket. The possibility of switching individual sockets finally makes remote control a reality. Your switch is my command!
- Magic of metering:
 - True RMS Current Metering & Reporting. Prevents overloaded circuits and allows allocating energy costs to specific devices. Monitor energy usage of each socket via the LED display, or from any remote location with the network management capabilities of the PDU.
- Real time alarm system:
 - Real time sensing of user defined alarm thresholds helps avoiding overloaded circuits. The PDU informs users about alarm situations via e-mail, SNMP, SysLog and visible (LED) and audible alarm signals.
- Protect you equipment:
 - Advanced circuit breaker protection helps protecting your valuable equipment.
- Wide product range:



Jellemzők

- Remote Power Management: Individual & Group Outlet Power Switching
- SNMP Control and SSL Web Browser (Https) for Setup and management
- Device Watchdog Reboot by Ping Action
- Remote Total PDU and Individual Outlet Power Monitoring
- True RMS Current Metering & Reporting
- Daily, Weekly, Monthly & Yearly Power Consumption Data
- Current, Temperature and Humidity Threshold Sensing
- User Defined Alarm Thresholds
- Alarm Notification via Email, SNMP, Syslog, LED or Audible Alarm.

Packaging

Darab / karton	1
Csomag térfogata, m3	0.026
Karton súlya, kg	4.6
Individual package size LxWxH:	165x330x480 mm
Carton size LxWxH:	165x330x480 mm
Származási hely	TW
Vonalkód	8716309067546
Customs code	8537109120

Tanúsítványok



Részletes leírás

RJ45:1pcs;10M Ethernet;ICMP, ARP, IP, TCP, UDP, DHCP, HTTP, HTTPS, SNMPv1

RJ11:1pcs;ENV Connection;private

Reset Hole:1pcs;Hardware Reset

Button:1pcs;Function1 beeps : Current, Temp./Humidity Display 2 Beeps : IP Display. 4 Beeps : DHCP/Fixed 6 Beeps : Reset to Default

Seven Segments:3 digits;Current True RMS Meter Range: 0A ~ 20 A

Resolution: 0.1A Precision: +/-2%+/-0.1AMP

IP;Press Button after 2 Beeps will display PDU IP Address

1 Digit;ID;0: Total Current 1~8: Individual Outlet Current t: Temperature h: Humidity

Green LED:8pcs;Power Status;Light when power on

Red LED:8pcs;Per Outlet Status;1. Flash: The load exceed the warning

setting 2. ON: The load exceed the overload setting 3. Off: Normal

Yellow LED:1pcs;Web Access;ON: SSL is enabled

Green LED:1pcs;IP;ON: DHCP is enabled

Output Socket:8pcs;IEC 320 C13

Input Connector:1pcs;IEC 320 C20

Circuit Breaker:2pcs;16 Amp

Nominal Voltage:160-320V

Voltage:230V

Max. Output Capacity:16 Amp

Frequency:50/60HZ full range

Temperature:0 ~ 45 Celsius degree

Humidity:0% ~ 90%