

## EnerGenie Programmable surge protector with LAN interface

EG-PMS2-LAN

### YOUR SWITCH IS MY COMMAND

- EG-PMS2-LAN is an advanced surge protector with power management features. It is possible to individually switch 4 sockets on or off manually via your local network or Internet, by timer schedule, or by programmable special events (eg: switch on my scanner whenever I start Photoshop, or have my printer switched on only when I really print). With your free personal user account on EnerGenie.com you can manage your EG-PMS2-LAN via Internet from all over the world, even with your smartphone.
- Stay in control of all your electrical devices at home or in the office
- Program four sockets individually via LAN or Internet
- Switch electric devices on or off with your smartphone, wherever you are
- Protect your valuable equipment
- An advanced standby-killer for computer peripherals
- Perfect solution for security systems , sauna , aquariums, pet habitats, etc.



### Features

- Switch individual sockets on/off manually from your computer
- Switch individual sockets on/off by a programmable timer schedule
- Switch individual sockets on/off whenever a certain software event occurs (e.g. Windows/other software start-up/shutdown, print spooler starting and finishing its job, etc)
- Because of the LAN interface and the built-in web-server, EG-PMS2-LAN can be accessed from any computer within your local network (via an Internet browser or Power manager software)

### Packaging

Q'ty in crtn, pcs	10
Crtn volume, CUM	0.04557
Crtn weight, kgs	12.16
Individual package size LxWxH:	400x145x60 mm
Carton size LxWxH:	420x350x310 mm
Country of origin	CN
Barcode	8716309074162
Customs code	8544429090

### Package contents

EG-PMS2-LAN  
User manual and Quick installation guide  
RJ45 cross-over cable (red), RJ45 LAN cable (grey)  
CD with Power Manager software for Windows

### Certificates



### Specifications

Input voltage: up to 250 VAC, 50 – 60 Hz  
Maximum load current: 10A  
Maximum power consumption: 2.5 W  
Built-in power supply  
Power cord: 1.8 m  
Surge protection: Type3, Up=1.2KV for L-N, Uoc=4KV for L-N Uo=230V  
Uc=250V Ucs=1.1X230V=253V  
Hardware schedule possibilities:  
Maximum number of independent hardware schedule events – 45 per socket  
  
Time setting accuracy in seconds  
Combine periodical and once events  
Timer accuracy: not more than 2 seconds error per day in case that power is always present. Otherwise there can be an additional up to 2 seconds error per each "power off"  
Indoor use only  
Dimensions: 378 x 98 x 55 mm  
Net weight: up to 1 kg

### System requirements

Local area network with RJ45 sockets  
Any Internet-enabled computer connected to the local area network  
Computer running Windows 7/8/10/11 is required for using the Power Manager software (use of this software is not compulsory)