CAT5e UTP Patch cord, black, 0.25 m

PP12-0.25M/BK



- Perfect connection
- For a reliable connection
- Gold plated contacts

Features

- Unshielded patch cord, 8P8C
- 50u" gold plated contacts
- Molded strain reliefs

Specifications

Category: Enhanced category 5
Type: UTP (unshielded)
Frequency bandwidth: Max. 100 MHz
Compliance with ANSI / TIA / EIA-568B standards
Conductor: AWG 26 (7 x 0.15 mm wire), CCA
Conductor insulation: HDPE 0.81 mm
Shielding: n/a
LDPE filler: n/a
Polyester tape: n/a
Drain wire: n/a
Jacket material: PVC
Jacket braiding: n/a
Jacket outer diameter: 5.0 mm
Length: conform item description
Color: conform item description

Packaging

Q'ty in crtn, pcs	300
Crtn volume, CUM	0.036
Crtn weight, kgs	4.95
Individual package size LxWxH:	110x105x10 mm
Carton size LxWxH:	400x300x300 mm
Country of origin	CN
Barcode	8716309074728
Customs code	8544421000

Certificates

Copyright © 2009–2022, Gembird Software Ltd.

Wittevrouwen 56 | 1358CD Almere | The Netherlands | Phone: +31-36-5211588 | www.cablexpert.com | postmaster@cablexpert.com