

## Rack 1500VA UPS

UPS-RACK-1500

### ULTIMATE DEFENCE

- Protects important data from power cuts
- Protects valuable equipment
- Protects users



### Features

- Automatic output voltage regulation (AVR)
- Rack 3.4U metal case
- USB control interface
- LCD display
- Short circuit protection
- Compatible with power generators of any brand
- Surge, spike and lightning protection
- Audible and visual alarms
- Overcharge and overdischarge protection

### Packaging

Q'ty in crtn, pcs	1
Crtn volume, CUM	0.04922
Crtn weight, kgs	15.9
Individual package size LxWxH:	535x400x230 mm
Carton size LxWxH:	535x400x230 mm
Country of origin	CN
Barcode	8716309074797
Customs code	8504408490

### Package contents

- UPS
- Power cord
- USB cable
- Software CD
- Spare fuse

### Specifications

UPS type: line interactive  
 Input: 220V AC  $\pm$  25%, 50Hz / 60Hz  $\pm$  10%  
 Output: 220V AC  $\pm$  10%, 50Hz / 60Hz  $\pm$  0.5% (on battery)  
 Switching time: no more than 10 ms (typically 6 ms)  
 Backup time: 8...20 mins (depends on the load)  
 Battery: 151 x 65 x 95 mm, sealed lead-acid 12 V / 8 Ah / 2.3 kg x 2 pcs  
 Charge time: up to 12 hours  
 Sockets: IEC13 output x 4 pcs, input IEC14, USB-BF control interface, telephone input/output  
 Operating conditions: 0°C~40°C, at humidity 10~90%RH non condensing  
 Noise: < 45 dB (at 1 meter distance)

### System requirements

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.

### Certificates

