

Rack 1500VA UPS

UPS-RACK-1500

ULTIMATE DEFENCE

- Protects important data from power cuts
- Protects valuable equipment
- Protects users



Funkcijos

- Automatic output voltage regulation (AVR)
- Rack 3.4U metal case
- USB control interface
- LCD display
- Short circuit protection
- Compatible with power generators of any brand
- Surge, spike and lightning protection
- Audible and visual alarms
- Overcharge and overdischarge protection

Packaging

Dėžių kiekis, vnt	1
Dėžių dydis, CUM	0.04922
Dėžių svoris, kg	15.9
Individual package size LxWxH:	535x400x230 mm
Kilmės šalis	535x400x230 mm
Kilmės šalis	CN
Brūkšninis kodas	8716309074797
Customs code	8504408590

Pakuotės turinys

UPS
Power cord
USB cable
Software CD
Spare fuse

Sertifikatai



Techniniai duomenys

UPS type: line interactive

Input: 220V AC $\pm 25\%$, 50Hz / 60Hz $\pm 10\%$

Output: 220V AC $\pm 10\%$, 50Hz / 60Hz $\pm 0.5\%$ (on battery)

Switching time: no more than 10 ms (typically 6 ms)

Backup time: 8...20 mins (depends on the load)

Battery: 151 x 65 x 95 mm, sealed lead-acid 12 V / 8 Ah / 2.3 kg x 2 pcs

Charge time: up to 12 hours

Sockets: IEC13 output x 4 pcs, input IEC14, USB-BF control interface, telephone input/output

Operating conditions: 0°C~40°C, at humidity 10~90%RH non condensing

Noise: < 45 dB (at 1 meter distance)

Power: 1500 VA (900 W)

Dimensions: 480 x 150 x 350 mm

Product weight: 15.8 kg

"Cold-start" function

Sistemos reikalavimai

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.