UPS rack 1500 VA

UPS-RACK-1500

- Optimale bescherming voor het nooit meer verliezen van je data na stroomuitval en het beschermt ook nog eens je kostbare apparatuur!



Kenmerken

- Automatische output voltage regulatie (AVR)
- USB interface
- LCD status indicatie
- Hooren zichtbaar alarm
- Bescherming tegen kortsluiting alsook blikseminslag
- Bescherming tegen stroompieken en -schommelingen
- Bescherming tegen overbelasting en -ontlading

Specificaties

UPS type: line interactive
Input: 220V AC ± 25%, 50Hz / 60Hz ± 10%
Output: 220V AC ± 10%, 50Hz / 60Hz ± 0.5% (on battery)
Switching time: no more than 10 ms (typically 6 ms)
Backup time: 8...20 mins (depends on the load)
Battery: 151 x 65 x 95 mm, sealed lead-acid 12 V / 8 Ah / 2.3 kg x 2 pcs

Charge time: up to 12 hours
Sockets: IEC13 output x 4 pcs, input IEC14, USB-BF control interface, telephone input\output
Operating conditions: 0°C~40°C, at humidity 10~90%RH non condensing

Noise: < 45 dB (at 1 meter distance)
Power: 1500 VA (900 W)
Dimensions: 480 x 150 x 350 mm
Product weight: 15.8 kg
"Cold-start" function

Verpakking

Verpakkingshoeveelheid/stuks	1
Volume doos/CUM	0.04922
Gewicht doos/kg	15.9
Afmetingen productverpakking LxBxH:	535x400x230 mm
Afmetingen transportverpakking LxBxH:	535x400x230 mm
Land van herkomst	CN
Streepjescode	8716309074797
Douanecode	8504408590

Inhoud verpakking

UPS
Power cord
USB cable
Software CD
Spare fuse

Certificaat/Certificaten

Systeemvereisten

In order to work correclty, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.

Copyright © 2009–2024, Gembird Software Ltd.

Wittevrouwen 56 | 1358CD Almere | The Netherlands | Phone: +31-36-5211588
www.energenie.com | postmaster@energenie.com