

SAI con AVR, 650 VA

EG-UPS-001

ULTIMATE DEFENCE

- Table top design
- Provides backup power prevents data loss
- Protects your sensitive and valuable equipment
- Compact and reliable ideal for home and small office use



Características

- Fuente de alimentación ininterrumpida de 650 VA con salida de onda sinusoidal modificada
- Regulación automática de voltaje AC (AVR)
- Protección inteligente contra sobrecargas, sobrecargas y cortocircuitos en los 4 enchufes
- Batería de respaldo de UPS en 2 enchufes (4 piezas opcionales)
- Alarmas sonoras y visuales
- Indicación de estado LED
- Gestión inteligente de la batería con protección contra sobrecargas y descargas
- Montaje en pared

Embalaje

Cantidad por caja, pcs	3
Volumen caja, M3	0.039251432
Peso caja, kgs	15.61
Medidas cajas individuales LxWxH:	329x150x240 mm
Medidas caja LxWxH	451x344x253 mm
País de origen	CN
Código de barras	8716309076081
codigo de aduanas	8504408590

Contenido de la caja

UPS
Power cord
User manual

Certificados



Especificaciones

Type: line interactive

Waveform: sine wave (AC mains), modified (square) sine wave (battery)

Input: 220 V AC $\pm 25\%$, 50 / 60 Hz $\pm 10\%$

Output: 220 V AC $\pm 10\%$, 50 / 60 Hz $\pm 1\%$ (220 V AC $\pm 5\%$ at inverter mode)

Switching time: less than 10 ms

Backup time: 10...30 mins (depends on the load)

Battery: sealed lead-acid 12 V DC / 7Ah

Charge time: up to 8 hours

Sockets: 1 x C13 (input), cable CEE 7/7P, 4 x Schuko (output)

Sockets with UPS: 2 pcs (optional 4 pcs)

Operating conditions: 0°C~40°C, at humidity 20~90%RH non condensing

Power: 650 VA (390 W)

Charging current: up to 1.2 A

Noise: < 45 dB at 1 m distance

Dimensions: 280 x 185 x 95 mm

Product weight: 4.5 kg

"Cold-start" function

Requisitos del sistema

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.