

UPS cu AVR, 650 VA

EG-UPS-001

ULTIMATE DEFENCE

- Table top design
- Provides backup power prevents data loss
- Protects your sensitive and valuable equipment
- Compact and reliable ideal for home and small office use



Features

- Sursa de alimentare neinteruptibila cu conector de iesire modificata de unda sinusoidală pură
- Reglare automata a tensiunii AC (AVR)
- Protecție inteligentă pentru supratensiune, supraincarcare și scurt circuite
- Alarmer vizuale și audio
- Indicator LED de stare
- Gestionare inteligentă a bateriei cu protecție pentru supraincarcare și supra-descarcare
- Montabil pe perete

Packaging

Q'ty in crtn, pcs	3
Crtn volume, CUM	0.039251432
Crtn weight, kgs	15.61
Individual package size LxWxH:	329x150x240 mm
Carton size LxWxH:	451x344x253 mm
Country of origin	CN
Barcode	8716309076081
Customs code	8504408590

Package contents

UPS
Power cord
User manual

Certificates



Specifications

Type: line interactive

Waveform: sine wave (AC mains), modified (square) sine wave (battery)

Input: 220 V AC $\pm 25\%$, 50 / 60 Hz $\pm 10\%$

Output: 220 V AC $\pm 10\%$, 50 / 60 Hz $\pm 1\%$ (220 V AC $\pm 5\%$ at inverter mode)

Switching time: less than 10 ms

Backup time: 10...30 mins (depends on the load)

Battery: sealed lead-acid 12 V DC / 7Ah

Charge time: up to 8 hours

Sockets: 1 x C13 (input), cable CEE 7/7P, 4 x Schuko (output)

Sockets with UPS: 2 pcs (optional 4 pcs)

Operating conditions: 0°C~40°C, at humidity 20~90%RH non condensing

Power: 650 VA (390 W)

Charging current: up to 1.2 A

Noise: < 45 dB at 1 m distance

Dimensions: 280 x 185 x 95 mm

Product weight: 4.5 kg

"Cold-start" function

System requirements

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.