

EnerGenie Programmable surge protector with GSM interface

EG-SMS

YOUR SWITCH IS MY COMMAND

- EG-SMS is an advanced surge protector with power management features. It is possible to individually switch 4 sockets on or off manually via SMS messages, by timer schedule, or by programmable sensors events (eg: switch sockets on/off when temperature is outside its selected range, a door is open or AC voltage is off). You can manage your EG-SMS via SMS messages from a GSM smartphone from all over the world.
- Stay in control of all your electrical devices at home or in the office
- Program four sockets individually via SMS messages from your smarphone
- Switch electric devices on or off with your smartphone, wherever you are
- Protect your valuable equipment
- Perfect solution for security systems, sauna, aquariums, pet habitats, etc.
- Easy control via the practical smartphone app

Vlastnosti

- Switch individual sockets on/off manually from your GSM smartphone
- Switch individual sockets on/off by a programmable timer schedule
- Get sensors info: temperature and relay contacts actions (closed and open)
- Switch individual sockets on/off by events from the sensors: if temperature is out its selected range, if door is open or if AC voltage is off
- Because of the GSM interface, EG-SMS can be accessed from any smartphone that is able to send SMS messages
- 64-bit password protected access

Packaging

Množství v kartonu, kusy Velikost kartonu, CUM Váha kartonu, kg Individual package size LxWxH: Carton size LxWxH: Země původu Čárkový kód (EAN) Customs code

Obsah balení

EG-SMS User manual GSM antenna

Certifikát



Copyright © 2009–2024, Gembird Software Ltd.

Wittevrouwen 56 | 1358CD Almere | The Netherlands | Phone: +31-36-5211588

www.energenie.com | postmaster@energenie.com

10 0.04545375 11.92 400x140x60 mm 425x345x310 mm CN 8716309076319 9028309000



Specifikace

Input voltage: 220 - 230 VAC, 50 - 60 Hz Maximum load: 10 A GSM support: 850/900/1800/1900 MHz networks Power supply: built-in adapter and Li-Ion battery Power consumption: up to 4.5 W Power cord: 1.8 m

Hardware schedule possibilities:

- Maximum number of independent hardware schedule events 10 per socket
- Time in seconds
- Timer accuracy: no more than 2 seconds error per day providing power is always present.
- Dimensions: 378 x 98 x 55 mm Net weight: 1 kg

Systémové požadavky

GSM 850/900/1800/1900 MHz SIM card, prepaid for SMS sending GSM Android v.2.1+ smartphone with a GSM SIM card prepaid for SMS sending