

Répéteur WIFI intelligent avec prise intégrée

EG-PM1W-001

YOUR SWITCH IS MY COMMAND

- EG-PM1W-001 is an easy to use WiFi Smart Home socket with powerful power management options. It enables you to switch the socket on or off via your home WiFi, Internet, by timer schedule, or by programmable special software events (eg: switch on my scanner whenever I start Photoshop, or have my printer switched on only when I really print). With your free personal user account on EnerGenie.com you can manage your EG-PM1W-001 via Internet from all over the world. The practical and easy to use PowerMan app allows you to control the socket from your smartphone.
- Stay in control of all your electric appliances
- Simply switch devices on or off with your smart phone or tablet
- Built-in WiFi repeater function -Optimal WiFi coverage ensured

Propriétés

- Point d'accès WIFI sans fil
- Intelligent et programmable
- Simple d'utilisation
- Répéteur WIFI 300 Mbps pour augmenter la portée.

Packaging

Q'ty in crtn, pcs Crtn volume, CUM Crtn weight, kgs Individual package size LxWxH: Carton size LxWxH: Country of origin Barcode Customs code 20 0.02634825 5.1 80x95x160 mm 430x285x215 mm CN 8716309076555 8544429090

Contenu du colis

EG-PM1W-001 User manual and Quick installation guide CD with Power Manager software for Windows

Certificats









Copyright © 2009-2024, Gembird Software Ltd.

Configuration requise

Local area network with a WLAN switch/router
Any Internet-enabled computer connected to the local area network
Computer running Windows® 2000/XP/Vist/Windows 7/8 is required for using
the Power Manager software (use of this software is not compulsory)



Spécificités

Interface: Wireless LAN IEEE 802.11 b/g/n protocols up to 300 Mbps

WLAN repeater mode
Input voltage: up to 250 VAC, 50 – 60 Hz
Maximum load current: 16 A
Maximum power consumption: 2.5 W
Hardware schedule possibilities:
Maximum number of independent hardware schedules 45
Time interval between the events – from 1 minute to 180 days

Loop period indays, hours, minutes or seconds (single loop period per socket)
Timer accuracy: not more than 2 seconds error per day

Clock synchronisation with NTP server Dimensions: 108 mm x 76 mm x 55 mm

Net weight: 0.15 kg