

EnerGenie Programmable surge protector with WLAN interface

EG-PMS2-WLAN

YOUR SWITCH IS MY COMMAND

- EG-PMS2-WLAN is an advanced surge protector with power management features. It is possible to individually switch 4 sockets on or off manually via your local WiFi network or Internet, by timer schedule, or by programmable special events (eg: switch on my scanner whenever I start Photoshop, or have my printer switched on only when I really print). With your free personal user account on EnerGenie.com you can manage your EG-PMS2-WLAN via Internet from all over the world, even with your smartphone.
- ⁻ Stay in control of all your electrical devices at home or in the office
- Program four sockets individually via WLAN or Internet
- Switch electric devices on or off with your smartphone, wherever you are
- Protect your valuable equipment
- An advanced standby-killer for computer peripherals
- Perfect solution for security systems, sauna, aquariums, pet habitats, etc.

Vlastnosti

- Switch individual sockets on/off manually from your computer
- Switch individual sockets on/off by a programmable timer schedule
- Switch individual sockets on/off whenever a certain software event occurs (e.g. Windows/other software start-up/shutdown, print spooler starting and finishing its job, etc)
- Because of the WLAN interface and the built-in web-server, EG-PMS2-WLAN can be accessed from any computer within your wireless local network (via an Internet browser or Power manager software)

Packaging

Množství v kartonu, kusy Velikost kartonu, CUM Váha kartonu, kg Individual package size LxWxH: Carton size LxWxH: Země původu Čárkový kód (EAN) Customs code 10 0.04545375 12.47 400x140x60 mm 425x345x310 mm CN 8716309076784 8536301090

Obsah balení

EG-PMS2-WLAN
USB cable
WLAN antenna
User manual and Quick installation guide
CD with Power Manager software for

Certifikát









Wittevrouwen 56 | 1358CD Almere | The Netherlands | Phone: +31-36-5211588

Copyright © 2009–2024, Gembird Software Ltd.



Specifikace

Input voltage: up to 250 VAC, 50 – 60 Hz

Maximum load current: 10 A

Maximum power consumption: 3.5 W

Surge protection: Type3, Up=1.2KV for L-N, Uoc=4KV for L-N Uo=230V

Uc=250V Ucs=1.1X230V=253V

Built-in power supply

Wireless LAN: IEEE 802.11 b/g Hardware schedule possibilities:

Maximum number of independent hardware schedule events – 45 per socket

Time setting accuracy in seconds

Combine periodical and once events

Timer accuracy: not more than 2 seconds error per day in case that power is always present. Otherwise there can be an additional up to 2 seconds error per each "power off"

Indoor use only

Dimensions: 378 x 98 x 55 mm

Net weight: up to 1 Kg

Systémové požadavky

Local area network with a WLAN switch/router For the initial setup and Power Manager software: Windows® 2000/XP/Vista or Windows 7/8 computer

Any Internet-enabled or WiFi-enabled computer or PDA and any Internet-