
FTP Cat6 Patch cord, pink, 0.5 m

PP6-0.5M/RO



Features

- CAT6 AWG26 stranded foil shielded patch cord with moulded strain relief 50u" 8P8C plugs, 0.5m
- Snagless boots

Specifications

Category: category 6
Type: FTP (foil shielded)
Frequency bandwidth: Max. 250 MHz
Compliance with ANSI / TIA / EIA-568B standards
Conductor: AWG 26 (7 x 0.15 mm wire), CCA
Conductor insulation: HDPE 0.86 mm
Shielding: AL foil
LDPE filler: yes
Polyester tape: yes
Drain wire: yes (7 x 0.12 mm CCA)
Jacket material: PVC
Jacket braiding: n/a
Jacket outer diameter: 6.2 mm
Length: conform item description
Color: conform item description

Packaging

Q'ty in crtn, pcs	300
Crtn volume, CUM	0.04
Crtn weight, kgs	7.86
Individual package size LxWxH:	150x120x10 mm
Carton size LxWxH:	400x300x330 mm
Country of origin	CN
Barcode	8716309077972
Customs code	8544421000

Certificates

Copyright © 2009–2022, Gembird Software Ltd.

Wittevrouwen 56 | 1358CD Almere | The Netherlands | Phone: +31-36-5211588 | www.cablexpert.com | postmaster@cablexpert.com