

Server power supply unit (1U), 250 W

CCC-PSU-1U-001

- Pure power for your server



Features

- 1U power supply unit for servers
- Active PFC
- Fully protected: over voltage protection, short-circuit protection, fan speed thermal Control
- Suitable for use with 19CC-1U-001 1U rack mount chassis

Packaging

Q'ty in crtn, pcs	12
Crtn volume, CUM	0.02
Crtn weight, kgs	9.92
Individual package size LxWxH:	220x85x45 mm
Carton size LxWxH:	510x360x110 mm
Country of origin	CN
Barcode	8716309079303
Customs code	8504403090

Specifications

MTBF: 100,000 hours
 Motherboard support: FLEX-ATX / TFX12V
 Input voltage: 115 230 V AC
 Input current: 4A at 115 VAC; 2A at 230 VAC
 Voltage frequency: 47 ~ 63 Hz
 Hold up time: 16 ms at full load
 Over voltage protection: +5 V Output, 7V Max; +3.3V Output, 4.3V Max; +12V Output, 15.6V Max
 Dimensions (L x W x H): 150 x 81.5 x 40.3 mm
 Operating / storage temperature: 0 ~ 40 / -20 ~ 60 Celsius degrees, 5 ~ 95% RH
 Connectors: 24 pin, 4 pin, SATA x 2 pcs, MOLEX x 1 pc, Floppy x 1 pcs

Certificates

