Server power supply unit (1U), 250 W

CCC-PSU-1U-001

- Pure power for your server



Jellemzők

- 1U power supply unit for servers
- Active PFC
- Fully protected: over voltage protection, short-circuit protection, fan speed thermal Control
- Suitable for use with 19CC-1U-001 1U rack mount chassis

Részletes leírás

MTBF: 100,000 hours
Motherboard support: FLEX-ATX / TFX12V
Input voltage: 115 230 V AC
Input current: 4A at 115 VAC; 2A at 230 VAC
Voltage frequency: 47 ~ 63 Hz
Hold up time: 16 ms at full load
Over voltage protection:+5 V Output, 7V Max; +3.3V Output, 4.3V Max; +12V Output, 15.6V Max
Dimensions (L x W x H): 150 x 81.5 x 40.3 mm
Operating / storage temperature: 0 ~ 40 / -20 ~ 60 Celsius degrees, 5 ~ 95% RH
Connectors: 24 pin, 4 pin, SATA x 2 pcs, MOLEX x 1 pc, Floppy x 1 pcs

Output + 5 V: + /5% 0.2 A up to 16 A
Output + 12 V: + /5% 0.6 A up to 17 A
Output 12 V: + /10% up to 0.8 A
Output + 3.3 V: + /5% 0.1 A up to 17 A
Output + 5 V standby: + /5% up to 2.3 A
Output power 3.3 V & 5 V combine load: 105 W
Total output power: up to 250 W

Packaging

Darab / karton	12
Csomag térfogata, m3	0.02
Karton súlya, kg	9.92
Individual package size LxWxH:	220x85x45 mm
Carton size LxWxH:	510x360x110 mm
Származási hely	CN
Vonalkód	8716309079303
Customs code	8536301090

Tanúsítványok

Copyright © 2009–2024, Gembird Software Ltd.
Wittevrouwen 56 | 1358CD Almere | The Netherlands | Phone: +31-36-5211588
www.energenie.com | postmaster@energenie.com