

FTP Cat6 LSZH patch cord, grey, 3 m

PP6-LSZH-3M


- Perfect connection
- Foil shielded for a reliable connection
- Low Smoke Zero Halogen (LSZH) jacket
- Gold plated contacts

Features

- Foil shielded patch cord, 8P8C
- Low Smoke Zero Halogen (LSZH) jacket
- Snagless boots

Packaging

Q'ty in crtn, pcs	100
Crtn volume, CUM	0.04
Crtn weight, kgs	8.66
Individual package size LxWxH:	200x140x10 mm
Carton size LxWxH:	400x300x330 mm
Country of origin	CN
Barcode	8716309080392
Customs code	8544421000



Specifications

Category: category 6
 Type: FTP (foil shielded)
 Frequency bandwidth: Max. 250 MHz
 Compliance with ANSI / TIA / EIA-568B standards
 Conductor: AWG 26 (7 x 0.15 mm wire), CCA
 Conductor insulation: HDPE 0.86 mm
 Shielding: AL foil
 LDPE filler: yes
 Polyester tape: yes
 Drain wire: yes (7 x 0.12 mm CCA)
 Jacket material: LSZH
 Jacket braiding: n/a
 Jacket outer diameter: 6.2 mm
 Length: conform item description
 Color: conform item description

Certificates

