
FTP Cat6 LSZH patch cord, grey, 5 m

PP6-LSZH-5M



- Perfect connection
- Foil shielded for a reliable connection
- Low Smoke Zero Halogen (LSZH) jacket
- Gold plated contacts

Features

- Foil shielded patch cord, 8P8C
- Low Smoke Zero Halogen (LSZH) jacket
- Snagless boots

Specifications

Category: category 6
Type: FTP (foil shielded)
Frequency bandwidth: Max. 250 MHz
Compliance with ANSI / TIA / EIA-568B standards
Conductor: AWG 26 (7 x 0.15 mm wire), CCA
Conductor insulation: HDPE 0.86 mm
Shielding: AL foil
LDPE filler: yes
Polyester tape: yes
Drain wire: yes (7 x 0.12 mm CCA)
Jacket material: LSZH
Jacket braiding: n/a
Jacket outer diameter: 6.2 mm
Length: conform item description
Color: conform item description

Packaging

Q'ty in crtn, pcs	50
Crtn volume, CUM	0.028
Crtn weight, kgs	7.3
Individual package size LxWxH:	40x140x140 mm
Carton size LxWxH:	400x305x230 mm
Country of origin	CN
Barcode	8716309080408
Customs code	8544421000

Certificates

Copyright © 2009–2022, Gembird Software Ltd.

Wittevrouwen 56 | 1358CD Almere | The Netherlands | Phone: +31-36-5211588 | www.cablexpert.com | postmaster@cablexpert.com