

Premium FTP Cat6 LSZH patch cord, grey, 2 m

PP6-LSZHCU-2M

- Perfect connection
- Foil shielded for a reliable connection
- Low Smoke Zero Halogen (LSZH) jacket
- Gold plated contacts

Features

- Foil shielded patch cord, 8P8C
- 50u" gold plated contacts
- Low Smoke Zero Halogen (LSZH) jacket
- Molded strain reliefs
- Snagless boots

Packaging

Q'ty in crtn, pcs	120
Crtn volume, CUM	0.041
Crtn weight, kgs	9.8
Individual package size LxWxH:	150x120x30 mm
Carton size LxWxH:	400x400x255 mm
Country of origin	CN
Barcode	8716309080422
Customs code	8544421000



Specifications

Category: category 6
 Type: FTP (foil shielded)
 Frequency bandwidth: Max. 250 MHz
 Compliance with ANSI / TIA / EIA-568B standards
 Conductor: AWG 26 (7 x 0.15 mm wire), CU
 Conductor insulation: HDPE 0.86 mm
 Shielding: AL foil
 LDPE filler: yes
 Polyester tape: yes
 Drain wire: yes (7 x 0.12 mm CCA)
 Jacket material: LSZH
 Jacket braiding: n/a
 Jacket outer diameter: 6.2 mm
 Length: conform item description
 Color: conform item description

Certificates

