

UPS con pantalla LCD y USB, 850 VA

EG-UPS-032

ULTIMATE DEFENCE

- Informative LCD display
- Provides backup power prevents data loss
- Protects your sensitive and valuable equipment
- Compact and reliable ideal for home and small office use



Características

- Ininterrumpible de alimentación 850 VA de potencia con salida de onda sinusoidal modificada
- Automático de tensión alterna regulación (AVR)
- Interfaz USB
- Inteligente sobretensión, sobrecarga y corto circuito de protección
- Las alarmas audibles y visuales
- LCD de indicación
- La gestión inteligente de la batería con protección de sobrecarga y sobre-descarga

Embalaje

Cantidad por caja, pcs	3
Volumen caja, M3	0.042042
Peso caja, kgs	19.94
Medidas cajas individuales LxWxH:	375x145x230 mm
Medidas caja LxWxH	455x385x240 mm
País de origen	CN
Código de barras	8716309080842
codigo de aduanas	8504408590

Contenido de la caja

UPS
Power cord
USB cable
Software CD
Spare fuse

Certificados



Especificaciones

Type: line interactive

Waveform: sine wave (AC mains), modified (square) sine wave (battery)

Input: 220 V AC $\pm 25\%$, 50 / 60 Hz $\pm 10\%$

Output: 220 V AC $\pm 10\%$, 50 / 60 Hz $\pm 1\%$ (220 V AC $\pm 5\%$ at inverter mode)

Switching time: less than 10 ms

Backup time: 8...20 mins (depends on the load)

Battery: sealed lead-acid 12 V DC / 8Ah

Charge time: up to 12 hours

Output sockets: 2 pcs x C13, 1 pc x german Shuko

USB control interface: BF socket

Operating conditions: 0°C ~ 40°C, at humidity 20 ~ 90 %RH non condensing

Power: 850 VA (510 W)

Charging current: up to 1.2 A

Noise: < 45 dB at 1 m distance

Dimensions: 340 x 95 x 165 mm

Product weight: 7 kg

"Cold-start" function

Requisitos del sistema

Software is compatible with Windows Vista, Windows 7/8, Windows 2008 server

In order to work correctly, the connected load should be at least 5% of the