

UPS with USB and LCD display, 850 VA, black

EG-UPS-032

ULTIMATE DEFENCE

- Informative LCD display
- Provides backup power prevents data loss
- Protects your sensitive and valuable equipment
- Compact and reliable ideal for home and small office use



Features

- Uninterruptable 850 VA power supply for PC's
- Automatic output voltage regulation (AVR)
- USB interface
- LCD status indication
- Short circuit protection
- Overload, surge, spike and lightning protection
- Audible and visual alarms
- Overcharge and overdischarge protection
- Including practical UPS Management software

Packaging

Q'ty in crtn, pcs	3
Crtn volume, CUM	0.042042
Crtn weight, kgs	19.94
Individual package size LxWxH:	375x145x230 mm
Carton size LxWxH:	455x385x240 mm
Country of origin	CN
Barcode	8716309080842
Customs code	8504408590

Package contents

UPS
Power cord
USB cable
Software CD
Spare fuse

Certificates



Specifications

Type: line interactive

Waveform: sine wave (AC mains), modified (square) sine wave (battery)

Input: 220 V AC $\pm 25\%$, 50 / 60 Hz $\pm 10\%$

Output: 220 V AC $\pm 10\%$, 50 / 60 Hz $\pm 1\%$ (220 V AC $\pm 5\%$ at inverter mode)

Switching time: less than 10 ms

Backup time: 8...20 mins (depends on the load)

Battery: sealed lead-acid 12 V DC / 8Ah

Charge time: up to 12 hours

Output sockets: 2 pcs x C13, 1 pc x german Shuko

USB control interface: BF socket

Operating conditions: 0°C ~ 40°C, at humidity 20 ~ 90 %RH non condensing

Power: 850 VA (510 W)

Charging current: up to 1.2 A

Noise: < 45 dB at 1 m distance

Dimensions: 340 x 95 x 165 mm

Product weight: 7 kg

"Cold-start" function

System requirements

Software is compatible with Windows Vista, Windows 7/8, Windows 2008 server

In order to work correctly, the connected load should be at least 5% of the