Джерело безперебійного живлення 850 Вольт-ампер з РК-дисплеєм та USB-інтерфейсом

EG-UPS-032



ULTIMATE DEFENCE

- Informative LCD display
- Provides backup power prevents data loss
- Protects your sensitive and valuable equipment
- Compact and reliable ideal for home and small office use

Особливості

- Джерело безперебійного живлення 850 Вольт-ампер
- Автоматичний регулятор вихідної напруги (AVR)
- USB-інтерфейс для управління і індикації
- РК-індикація стану
- Захист від короткого замикання
- Захист від викидів напруги, перешкод і блискавок
- Звукове і візуальне сповіщення про події
- Захист батареї від перезаряду і глибокого розряду

Специфікація

Type: line interactive
Waveform: sine wave (AC mains), modified (square) sine wave (battery)

Input: 220 V AC ± 25%, 50 / 60 Hz ± 10%
Output: 220 V AC ± 10%, 50 / 60 Hz ± 1% (220 V AC ± 5 % at inverter mode)

Switching time: less than 10 ms
Backup time: 8...20 mins (depends on the load)
Battery: sealed lead-acid 12 V DC / 8Ah
Charge time: up to 12 hours
Output sockets: 2 pcs x C13, 1 pc x german Shuko
USB control interface: BF socket
Operating conditions: 0°C ~ 40°C, at humidity 20 ~ 90 %RH non condensing

Power: 850 VA (510 W)
Charging current: up to 1.2 A
Noise: < 45 dB at 1 m distance
Dimensions: 340 x 95 x 165 mm
Product weight: 7 kg
"Cold-start" function

Пакування

Кількість в коробці, шт.	3
Об'єм коробки, куб. м	0.042042
Вага коробки, кг	19.94
Розмір індивідуальної упаковки ДхШхВ:	375x145x230 mm
Розмір коробки ДхШхВ:	455x385x240 mm
Країна виробник	CN
Штрих-код	8716309080842
Митний-код	8504408590

Комплектація

UPS
Power cord
USB cable
Software CD
Spare fuse

Сертифікати

Системні вимоги

Software is compatible with Windows Vista, Windows 7/8, Windows 2008 server

In order to work correclty, the connected load should be at least 5% of the

Copyright © 2009–2024, Gembird Software Ltd.

Wittevrouwen 56 | 1358CD Almere | The Netherlands | Phone: +31-36-5211588
www.energenie.com | postmaster@energenie.com