

## UPS with USB and LCD display, 1200 VA, black

EG-UPS-033

### ULTIMATE DEFENCE

- Informative LCD display
- Provides backup power prevents data loss
- Protects your sensitive and valuable equipment
- Compact and reliable ideal for home and small office use



### Features

- Uninterruptable 1200 VA power supply for PC's
- Automatic output voltage regulation (AVR)
- USB interface
- LCD status indication
- Short circuit protection
- Surge, spike and lightning protection
- Audible and visual alarms
- Overcharge and overdischarge protection
- Including practical UPS Management software

### Packaging

|                                |                |
|--------------------------------|----------------|
| Q'ty in crtn, pcs              | 2              |
| Crtn volume, CUM               | 0,04575        |
| Crtn weight, kgs               | 21.2           |
| Individual package size LxWxH: | 450x180x295 mm |
| Carton size LxWxH:             | 375x400x305 mm |
| Country of origin              | CN             |
| Barcode                        | 8716309080873  |
| Customs code                   | 8504408490     |

### Package contents

UPS  
Power cord  
USB cable  
Software CD  
Spare fuse

### Specifications

Type: line interactive  
Waveform: sine wave (AC mains), modified (square) sine wave (battery)  
Input: 220 V AC  $\pm$  25%, 50 / 60 Hz  $\pm$  10%  
Output: 220 V AC  $\pm$  10%, 50 / 60 Hz  $\pm$  1% (220 V AC  $\pm$  5 % at inverter mode)  
Switching time: less than 10 ms  
Backup time: 8...20 mins (depends on the load)  
Battery: sealed lead-acid 12 V DC / 7 Ah x 2 pcs (connected in series)

Charge time: up to 12 hours  
Output sockets: 3 pcs x C13, 2 pcs x german Shuko  
USB control interface: BF socket

### System requirements

Software is compatible with Windows Vista, Windows 7/8, Windows 2008 server

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.

### Certificates

