

# UPS with USB and LCD display, 1200 VA, black

**EG-UPS-033** 



**Specifications** 

Type: line interactive

Input: 220 V AC  $\pm$  25%, 50 / 60 Hz  $\pm$  10%

Backup time: 8...20 mins (depends on the load)

Output sockets: 3 pcs x C13, 2 pcs x german Shuko

Switching time: less than 10 ms

Charge time: up to 12 hours

Power: 1200 VA (720 W) Charging current: up to 1.2 A Noise: < 45 dB at 1 m distance Dimensions: 400 x 125 x 220 mm

Net weight: 10.4 kg "Cold-start" function

USB control interface: BF socket

#### **ULTIMATE DEFENCE**

- Informative LCD display
- Provides backup power prevents data loss
- Protects your sensitive and valuable equipment
- Compact and reliable ideal for home and small office use

### **Features**

- Uninterruptable 1200 VA power supply for PC's
- Automatic output voltage regulation (AVR)
- USB interface
- LCD status indication
- Short circuit protection
- Overload, surge, spike and lightning protection
- Audible and visual alarms
- Overcharge and overdischarge protection
- Including practical UPS Management software

# **Packaging**

Q'ty in crtn, pcs Crtn volume, CUM Crtn weight, kgs Individual package size LxWxH: Carton size LxWxH: Country of origin Barcode Customs code 2 0.04575 26.38 450x180x295 mm 375x400x305 mm CN 8716309080873 8504408590

## **Package contents**

UPS Power cord USB cable Software CD Spare fuse

#### Certificates









# **System requirements**

Software is compatible with Windows Vista, Windows 7/8, Windows 2008 server, windows 10/11

Waveform: sine wave (AC mains), modified (square) sine wave (battery)

Output: 220 V AC  $\pm$  10%, 50 / 60 Hz  $\pm$  1% (220 V AC  $\pm$  5 % at inverter mode)

Operating conditions: 0°C ~ 40°C, at humidity 20 ~ 90 %RH non condensing

Battery: sealed lead-acid 12 V DC / 7 Ah x 2 pcs(connected in series)

Copyright © 2009-2024, Gembird Software Ltd.