UPS con pantalla LCD y USB, 1200 VA

EG-UPS-033



ULTIMATE DEFENCE

- Informative LCD display
- Provides backup power prevents data loss
- Protects your sensitive and valuable equipment
- Compact and reliable ideal for home and small office use

Características

- Ininterrumpible de alimentación 1200 VA de potencia con salida de onda sinusoidal modificada
- Automático de tensión alterna regulación (AVR)
- Interfaz USB
- Inteligente sobretensión, sobrecarga y corto circuito de protección

- Las alarmas audibles y visuales
- LCD de indicación
- La gestión inteligente de la batería con protección de sobrecarga y sobre-descarga

Embalaje

Cantidad por caja, pcs	2
Volumen caja, M3	0.04575
Peso caja, kgs	26.38
Medidas cajas individuales LxWxH:	450x180x295 mm
Medidas caja LxWxH	375x400x305 mm
Pais de origen	CN
Código de barras	8716309080873
codigo de aduanas	8504408590

Contenido de la caja

UPS
Power cord
USB cable
Software CD
Spare fuse

Certificados

Especificaciones

Type: line interactive
Waveform: sine wave (AC mains), modified (square) sine wave (battery)

Input: 220 V AC ± 25%, 50 / 60 Hz ± 10%
Output: 220 V AC ± 10%, 50 / 60 Hz ± 1% (220 V AC ± 5 % at inverter mode)

Switching time: less than 10 ms
Backup time: 8...20 mins (depends on the load)
Battery: sealed lead-acid 12 V DC / 7 Ah x 2 pcs(connected in series)

Charge time: up to 12 hours
Output sockets: 3 pcs x C13, 2 pcs x german Shuko
USB control interface: BF socket
Operating conditions: 0°C ~ 40°C, at humidity 20 ~ 90 %RH non condensing

Power: 1200 VA (720 W)
Charging current: up to 1.2 A
Noise: < 45 dB at 1 m distance
Dimensions: 400 x 125 x 220 mm
Net weight: 10.4 kg
"Cold-start" function

Requisitos del sistema

Software is compatible with Windows Vista, Windows 7/8, Windows 2008 server, windows 10/11

Copyright © 2009–2024, Gembird Software Ltd.

Wittevrouwen 56 | 1358CD Almere | The Netherlands | Phone: +31-36-5211588
www.energenie.com | postmaster@energenie.com