

## UPS with USB and LCD display, 1200 VA, black

EG-UPS-033

### ULTIMATE DEFENCE

- Informative LCD display
- Provides backup power prevents data loss
- Protects your sensitive and valuable equipment
- Compact and reliable ideal for home and small office use



### Īpašības

- Uninterruptable 1200 VA power supply for PC's
- Automatic output voltage regulation (AVR)
- USB interface
- LCD status indication
- Short circuit protection
- Overload, surge, spike and lightning protection
- Audible and visual alarms
- Overcharge and overdischarge protection
- Including practical UPS Management software

### Packaging

Skaitis iepakojumā, gab.  
Iepakojuma izmērs, kub.m  
Iepakojuma svars, kg  
Individual package size LxWxH:  
Carton size LxWxH:  
Izcelsmes valsts  
Svītrkods  
Customs code

2  
0.04575  
26.38  
450x180x295 mm  
375x400x305 mm  
CN  
8716309080873  
8504408590

### Iepakojuma saturs

UPS  
Power cord  
USB cable  
Software CD  
Spare fuse

### Sertifikāti



### Specifikācija

Type: line interactive

Waveform: sine wave (AC mains), modified (square) sine wave (battery)

Input: 220 V AC  $\pm$  25%, 50 / 60 Hz  $\pm$  10%

Output: 220 V AC  $\pm$  10%, 50 / 60 Hz  $\pm$  1% (220 V AC  $\pm$  5 % at inverter mode)

Switching time: less than 10 ms

Backup time: 8...20 mins (depends on the load)

Battery: sealed lead-acid 12 V DC / 7 Ah x 2 pcs (connected in series)

Charge time: up to 12 hours

Output sockets: 3 pcs x C13, 2 pcs x german Shuko

USB control interface: BF socket

Operating conditions: 0°C ~ 40°C, at humidity 20 ~ 90 %RH non condensing

Power: 1200 VA (720 W)

Charging current: up to 1.2 A

Noise: < 45 dB at 1 m distance

Dimensions: 400 x 125 x 220 mm

Net weight: 10.4 kg

"Cold-start" function

### Sistēmas prasības

Software is compatible with Windows Vista, Windows 7/8, Windows 2008 server, windows 10/11