

1200VA UPS mit LCD

EG-UPS-033

ULTIMATE DEFENCE

- Informative LCD display
- Provides backup power prevents data loss
- Protects your sensitive and valuable equipment
- Compact and reliable ideal for home and small office use



Eigenschaften

- Automatische Ausgangsspannungsregulierung (AVR)
- USB Schnittstelle
- LCD-Statusanzeige
- Kurzschlussicherung
- Überspannungsund Spannungsspitzenabsicherung sowie Blitzschutz
- Hörbare und sichtbare Alarmer
- Absicherung vor Überladung und Tiefentladung

Verpackungsdetails

Stückzahl pro Karton	2
Karton Volumen, m ³	0.04575
Kartongewicht, kg	26.38
Abmessungen Verpackung (LxBxH):	450x180x295 mm
Abmessungen Umkarton (LxBxH):	375x400x305 mm
Ursprungsland	CN
EAN Code	8716309080873
Zolltarif-Nr.:	8504408590

Lieferumfang

UPS
Power cord
USB cable
Software CD
Spare fuse

CE-Erklärung



Spezifikationen

Type: line interactive

Waveform: sine wave (AC mains), modified (square) sine wave (battery)

Input: 220 V AC $\pm$ 25%, 50 / 60 Hz $\pm$ 10%

Output: 220 V AC $\pm$ 10%, 50 / 60 Hz $\pm$ 1% (220 V AC $\pm$ 5 % at inverter mode)

Switching time: less than 10 ms

Backup time: 8...20 mins (depends on the load)

Battery: sealed lead-acid 12 V DC / 7 Ah x 2 pcs (connected in series)

Charge time: up to 12 hours

Output sockets: 3 pcs x C13, 2 pcs x german Shuko

USB control interface: BF socket

Operating conditions: 0°C ~ 40°C, at humidity 20 ~ 90 %RH non condensing

Power: 1200 VA (720 W)

Charging current: up to 1.2 A

Noise: < 45 dB at 1 m distance

Dimensions: 400 x 125 x 220 mm

Net weight: 10.4 kg

"Cold-start" function

Systemvoraussetzungen

Software is compatible with Windows Vista, Windows 7/8, Windows 2008 server, windows 10/11