# 1200 VA UPS con LCD

EG-UPS-033




## ULTIMATE DEFENCE

- Informative LCD display
- Provides backup power prevents data loss
- Protects your sensitive and valuable equipment
- Compact and reliable ideal for home and small office use

## Caratteristiche

- Regolazione automatica del voltaggio in output (AVR)
- Interfaccia USB
- Indicatori status del LCD
- Protezione da corto circuiti
- Protezione da sovraccarichi e fulmini
- Allarmi sonori e visivi
- Protezione da sovraccaricamento e sovrascaricamento

## Specifiche

Type: line interactive
Waveform: sine wave (AC mains), modified (square) sine wave (battery)

Input: 220 V AC ± 25%, 50 / 60 Hz ± 10%
Output: 220 V AC ± 10%, 50 / 60 Hz ± 1% (220 V AC ± 5 % at inverter mode)

Switching time: less than 10 ms
Backup time: 8...20 mins (depends on the load)
Battery: sealed lead-acid 12 V DC / 7 Ah x 2 pcs(connected in series)

Charge time: up to 12 hours
Output sockets: 3 pcs x C13, 2 pcs x german Shuko
USB control interface: BF socket
Operating conditions: 0°C ~ 40°C, at humidity 20 ~ 90 %RH non condensing

Power: 1200 VA (720 W)
Charging current: up to 1.2 A
Noise: < 45 dB at 1 m distance
Dimensions: 400 x 125 x 220 mm
Net weight: 10.4 kg
"Cold-start" function

## Confezione

| | |
|---|---|
| Quantità per cartone, pezzi | 2 |
| Volume del cartone, CUM | 0.04575 |
| Peso del cartone, Kg | 26.38 |
| Individual package size LxWxH: | 450x180x295 mm |
| Carton size LxWxH: | 375x400x305 mm |
| Paese di origine | CN |
| Barcode | 8716309080873 |
| Customs code | 8504408590 |

## Contenuto della Confezione

UPS
Power cord
USB cable
Software CD
Spare fuse

## Certificazioni

## Requisiti di sistema

Software is compatible with Windows Vista, Windows 7/8, Windows 2008 server, windows 10/11

Copyright © 2009–2024, Gembird Software Ltd.

Wittevrouwen 56 | 1358CD Almere | The Netherlands | Phone: +31-36-5211588
www.energenie.com | postmaster@energenie.com