UPS with USB and LCD display, 1200 VA, black

EG-UPS-033



ULTIMATE DEFENCE

- Informative LCD display
- Provides backup power prevents data loss
- Protects your sensitive and valuable equipment
- Compact and reliable ideal for home and small office use

Vlastnosti

- Uninterruptable 1200 VA power supply for PC's
- Automatic output voltage regulation (AVR)
- USB interface
- LCD status indication
- Short circuit protection
- Overload, surge, spike and lightning protection
- Audible and visual alarms
- Overcharge and overdischarge protection
- Including practical UPS Management software

Specifikace

Type: line interactive
Waveform: sine wave (AC mains), modified (square) sine wave (battery)

Input: 220 V AC ± 25%, 50 / 60 Hz ± 10%
Output: 220 V AC ± 10%, 50 / 60 Hz ± 1% (220 V AC ± 5 % at inverter mode)

Switching time: less than 10 ms
Backup time: 8...20 mins (depends on the load)
Battery: sealed lead-acid 12 V DC / 7 Ah x 2 pcs(connected in series)

Charge time: up to 12 hours
Output sockets: 3 pcs x C13, 2 pcs x german Shuko
USB control interface: BF socket
Operating conditions: 0°C ~ 40°C, at humidity 20 ~ 90 %RH non condensing

Power: 1200 VA (720 W)
Charging current: up to 1.2 A
Noise: < 45 dB at 1 m distance
Dimensions: 400 x 125 x 220 mm
Net weight: 10.4 kg
"Cold-start" function

Packaging

Množství v kartonu, kusy	2
Velikost kartonu, CUM	0.04575
Váha kartonu, kg	26.38
Individual package size LxWxH:	450x180x295 mm
Carton size LxWxH:	375x400x305 mm
Země původu	CN
Čárkový kód (EAN)	8716309080873
Customs code	8504408590

Obsah balení

UPS
Power cord
USB cable
Software CD
Spare fuse

Certifikát

Systémové požadavky

Software is compatible with Windows Vista, Windows 7/8, Windows 2008 server, windows 10/11

Copyright © 2009–2024, Gembird Software Ltd.

Wittevrouwen 56 | 1358CD Almere | The Netherlands | Phone: +31-36-5211588
www.energenie.com | postmaster@energenie.com