

UPS with USB and LCD display, 1500 VA, black

EG-UPS-034



ULTIMATE DEFENCE

- Informative LCD display
- Provides backup power prevents data loss
- Protects your sensitive and valuable equipment
- Compact and reliable ideal for home and small office use

Features

- Uninterruptable 1500 VA power supply for PC's
- Automatic output voltage regulation (AVR)
- USB interface
- LCD status indication
- Short circuit protection
- Overload, surge, spike and lightning protection
- Audible and visual alarms
- Overcharge and overdischarge protection
- Including practical UPS Management software

Packaging

Q'ty in crtn, pcs Crtn volume, CUM Crtn weight, kgs Individual package size LxWxH: Carton size LxWxH: Country of origin Barcode Customs code 2 0.0457805 25.3 450x180x295 mm 380x395x305 mm CN 8716309080880 8504408590

Package contents

UPS Power cord USB cable Software CD Spare fuse

Certificates









Copyright © 2009-2025, Gembird Software Ltd.

Specifications

Type: line interactive

Waveform: sine wave (AC mains), modified (square) sine wave (battery)

Input: 220 V AC ± 25%, 50 / 60 Hz ± 10%

Output: 220 V AC \pm 10%, 50 / 60 Hz \pm 1% (220 V AC \pm 5 % at inverter mode)

Switching time: less than 10 ms

Backup time: 8...20 mins (depends on the load)

Battery: sealed lead-acid 12 V DC / 8 Ah x 2 pcs(connected in series)

Charge time: up to 12 hours

Sockets: built-in input cable, 3 pcs x C13 output, 2 pcs x german Shuko

USB control interface: BF socket

Operating conditions: 0°C ~ 40°C, at humidity 20 ~ 90 %RH non condensing

Power: 1500 VA (900 W) Charging current: up to 1.2 A Noise: < 45 dB at 1 m distance Dimensions: 400 x 125 x 220 mm

Net weight: 10.8 kg "Cold-start" function

System requirements

Software is compatible with Windows Vista, Windows 7/8/10/11, Windows 2008 server

In order to work correctty, the connected load should be at least 5% of the