

UPS with USB and LCD display, 1500 VA, black

EG-UPS-034

ULTIMATE DEFENCE

- Informative LCD display
- Provides backup power prevents data loss
- Protects your sensitive and valuable equipment
- Compact and reliable ideal for home and small office use



Features

- Uninterruptable 1500 VA power supply for PC's
- Automatic output voltage regulation (AVR)
- USB interface
- LCD status indication
- Short circuit protection
- Surge, spike and lightning protection
- Audible and visual alarms
- Overcharge and overdischarge protection
- Including practical UPS Management software

Packaging

| | |
|--------------------------------|----------------|
| Q'ty in crtn, pcs | 2 |
| Crtn volume, CUM | 0,0457805 |
| Crtn weight, kgs | 25.3 |
| Individual package size LxWxH: | 450x180x295 mm |
| Carton size LxWxH: | 380x395x305 mm |
| Country of origin | CN |
| Barcode | 8716309080880 |
| Customs code | 8504408490 |

Package contents

UPS
Power cord
USB cable
Software CD
Spare fuse

Specifications

Type: line interactive
Waveform: sine wave (AC mains), modified (square) sine wave (battery)
Input: 220 V AC \pm 25%, 50 / 60 Hz \pm 10%
Output: 220 V AC \pm 10%, 50 / 60 Hz \pm 1% (220 V AC \pm 5 % at inverter mode)
Switching time: less than 10 ms
Backup time: 8...20 mins (depends on the load)
Battery: sealed lead-acid 12 V DC / 8 Ah x 2 pcs (connected in series)
Charge time: up to 12 hours
Sockets: 1 x C14 input, 3 pcs x C13 output, 2 pcs x german Shuko

System requirements

Software is compatible with Windows Vista, Windows 7/8, Windows 2008 server
In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.

Certificates

