

UPS con pantalla LCD y USB, 1500 VA

EG-UPS-034

ULTIMATE DEFENCE

- Informative LCD display
- Provides backup power prevents data loss
- Protects your sensitive and valuable equipment
- Compact and reliable ideal for home and small office use



Características

- Ininterrumpible de alimentación 1500 VA de potencia con salida de onda sinusoidal modificada
- Automático de tensión alterna regulación (AVR)
- Interfaz USB
- Inteligente sobretensión, sobrecarga y corto circuito de protección
- Las alarmas audibles y visuales
- LCD de indicación
- La gestión inteligente de la batería con protección de sobrecarga y sobre-descarga

Embalaje

Cantidad por caja, pcs	2
Volumen caja, M3	0.0457805
Peso caja, kgs	25.3
Medidas cajas individuales LxWxH:	450x180x295 mm
Medidas caja LxWxH	380x395x305 mm
País de origen	CN
Código de barras	8716309080880
codigo de aduanas	8504408590

Contenido de la caja

UPS
Power cord
USB cable
Software CD
Spare fuse

Certificados



Especificaciones

Type: line interactive

Waveform: sine wave (AC mains), modified (square) sine wave (battery)

Input: 220 V AC $\pm$ 25%, 50 / 60 Hz $\pm$ 10%

Output: 220 V AC $\pm$ 10%, 50 / 60 Hz $\pm$ 1% (220 V AC $\pm$ 5 % at inverter mode)

Switching time: less than 10 ms

Backup time: 8...20 mins (depends on the load)

Battery: sealed lead-acid 12 V DC / 8 Ah x 2 pcs (connected in series)

Charge time: up to 12 hours

Sockets: built-in input cable, 3 pcs x C13 output, 2 pcs x german Shuko

USB control interface: BF socket

Operating conditions: 0°C ~ 40°C, at humidity 20 ~ 90 %RH non condensing

Power: 1500 VA (900 W)

Charging current: up to 1.2 A

Noise: < 45 dB at 1 m distance

Dimensions: 400 x 125 x 220 mm

Net weight: 10.8 kg

"Cold-start" function

Requisitos del sistema

Software is compatible with Windows Vista, Windows 7/8, Windows 2008 server

In order to work correctly, the connected load should be at least 5% of the