

UPS with USB and LCD display, 1500 VA, black

EG-UPS-034

ULTIMATE DEFENCE

- Informative LCD display
- Provides backup power prevents data loss
- Protects your sensitive and valuable equipment
- Compact and reliable ideal for home and small office use



Jellemzők

- Uninterruptable 1500 VA power supply for PC's
- Automatic output voltage regulation (AVR)
- USB interface
- LCD status indication
- Short circuit protection
- Overload, surge, spike and lightning protection
- Audible and visual alarms
- Overcharge and overdischarge protection
- Including practical UPS Management software

Packaging

Darab / karton	2
Csomag térfogata, m3	0.0457805
Karton súlya, kg	25.3
Individual package size LxWxH:	450x180x295 mm
Carton size LxWxH:	380x395x305 mm
Származási hely	CN
Vonalkód	8716309080880
Customs code	8504408590

Csomag tartalom

UPS
Power cord
USB cable
Software CD
Spare fuse

Tanúsítványok



Részletes leírás

Type: line interactive

Waveform: sine wave (AC mains), modified (square) sine wave (battery)

Input: 220 V AC $\pm 25\%$, 50 / 60 Hz $\pm 10\%$

Output: 220 V AC $\pm 10\%$, 50 / 60 Hz $\pm 1\%$ (220 V AC $\pm 5\%$ at inverter mode)

Switching time: less than 10 ms

Backup time: 8...20 mins (depends on the load)

Battery: sealed lead-acid 12 V DC / 8 Ah x 2 pcs (connected in series)

Charge time: up to 12 hours

Sockets: built-in input cable, 3 pcs x C13 output, 2 pcs x german Shuko

USB control interface: BF socket

Operating conditions: 0°C ~ 40°C, at humidity 20 ~ 90 %RH non condensing

Power: 1500 VA (900 W)

Charging current: up to 1.2 A

Noise: < 45 dB at 1 m distance

Dimensions: 400 x 125 x 220 mm

Net weight: 10.8 kg

"Cold-start" function

Rendszerkövetelmények

Software is compatible with Windows Vista, Windows 7/8, Windows 2008 server

In order to work correctly, the connected load should be at least 5% of the