UPS with USB and LCD display, 1500 VA, black

EG-UPS-034



ULTIMATE DEFENCE

- Informative LCD display
- Provides backup power prevents data loss
- Protects your sensitive and valuable equipment
- Compact and reliable ideal for home and small office use

Features

- Uninterruptable 1500 VA power supply for PC's
- Automatic output voltage regulation (AVR)
- USB interface
- LCD status indication
- Short circuit protection
- Overload, surge, spike and lightning protection
- Audible and visual alarms
- Overcharge and overdischarge protection
- Including practical UPS Management software

Specifications

Type: line interactive
Waveform: sine wave (AC mains), modified (square) sine wave (battery)

Input: 220 V AC ± 25%, 50 / 60 Hz ± 10%
Output: 220 V AC ± 10%, 50 / 60 Hz ± 1% (220 V AC ± 5 % at inverter mode)

Switching time: less than 10 ms
Backup time: 8...20 mins (depends on the load)
Battery: sealed lead-acid 12 V DC / 8 Ah x 2 pcs(connected in series)

Charge time: up to 12 hours
Sockets: built-in input cable, 3 pcs x C13 output, 2 pcs x german Shuko

USB control interface: BF socket
Operating conditions: 0°C ~ 40°C, at humidity 20 ~ 90 %RH non condensing

Power: 1500 VA (900 W)
Charging current: up to 1.2 A
Noise: < 45 dB at 1 m distance
Dimensions: 400 x 125 x 220 mm
Net weight: 10.8 kg
"Cold-start" function

Packaging

Q'ty in crtn, pcs	2
Crtn volume, CUM	0.0457805
Crtn weight, kgs	25.3
Individual package size LxWxH:	450x180x295 mm
Carton size LxWxH:	380x395x305 mm
Country of origin	CN
Barcode	8716309080880
Customs code	8504408590

Package contents

UPS
Power cord
USB cable
Software CD
Spare fuse

Certificates

System requirements

Software is compatible with Windows Vista, Windows 7/8, Windows 2008 server

In order to work correclty, the connected load should be at least 5% of the

Copyright © 2009–2024, Gembird Software Ltd.

Wittevrouwen 56 | 1358CD Almere | The Netherlands | Phone: +31-36-5211588
www.energenie.com | postmaster@energenie.com