

Digital to analog audio converter

DSC-OPT-RCA-001

- Bridges the gap between digital and analog audio
- Perfect for connecting your Blu-ray player to your home stereo
- Easy installation



Features

- Allows using digital audio devices with analogue audio receivers or amplifiers
- Converts a digital Coaxial or Toslink audio signal to analogue stereo audio (L/R)

60

14

CN

0.042642

180x100x30 mm

8716309082570

8517620000

515x345x240 mm

- Standard RCA (cinch) audio output connectors
- Electromagnetic noise-free transmission
- 5 V DC power supply included

Specifications

Input audio formats: sampling rate at 32, 44.1, 48 and 96 KHz, 24-bit S/PDIF incoming bit stream on left and right channels

Input: 1 x RCA (Coaxial); 1 x Toslink Output: 2 x RCA audio (L/R) Power supply: 5 V DC up to 2 A Power consumption: 0.5 W max Operating temperature: 0 70 ? Dimensions: 51 x 41 x 26 mm Net weight: 78 g

Packaging

Q'ty in crtn, pcs Crtn volume, CUM Crtn weight, kgs Individual package size LxWxH: Carton size LxWxH: Country of origin Barcode Customs code

Package contents

Converter Power adapter User manual

Certificates







